THIS DRAWING AND SPECIFICATIONS ARE THE PROPERTY OF REOTEMP REOTEMP REOTEMP Instrument Corporation INSTRUMENT CORP., AND ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT 10656 Roselle Street San Diego, CA 92121 USA Phone: (858) 784-0710 BE REPRODUCED, COPIED OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF ITEMS DEPICTED HEREIN WITHOUT WRITTEN PERMISSION FROM REOTEMP INSTRUMENT CORP. **INSTRUMENTS** 3rd ANGLE PROJECTION Fax: (858) 784-0720 CUSTOMER'S NAME: CUSTOMER'S P.O. NO.: REOTEMP ORDER NO.: DATE: CERTIFIED BY: Ø5.1 [130]-1.9 [49] .19 [5]→ .27 [7] −1.5 [37]**-**► Ø4.3 [109] -FILL PLUG Ø3.6 [92] **AISI 316** 3/4" HEX 3.9 [100] -1/4" NPT **REOTEMP** -.9 [22] .8 [19] -3.3 [84]-**REVISIONS** DATE APPROVED **REV DESCRIPTION** 4/25/17 INITIAL RELEASE MN UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES & [mm] TOLERANCES ARE: PART NAME: DATE: CASE MATERIAL: 304SS 4/25/17 PR 40 1/4" NPT BACK CONNECT FRACTIONS DECIMALS ANGLES DRAWN BY: WETTED MATERIAL: 316LSS $.X \pm .2 \pm 5$ ±1/32 MNeill WITH FRONT FLANGE $.XX \pm .01$ $.XXX \pm .005$ APPROVED: POINTER: MICRO-ADJUSTABLE SURFACE FINISH 63 MN PART NO: SIZE: CAGE CODE: DWG NO: REV: **ENCLOSURE RATING: IP67/NEMA 4X** 24793 20167 X1 PR40S1E4L20-G-T FIRST USED ON: SCALE: NTS FILE NAME: SHEET 1 OF 1